

SUN SHINE 38

TEAM AND OWNER'S VERSION

Engine

Engine supplied (refer to price-list)
 Foam soundproofing
 Battery 70 A/H
 Access through companionway
 Continual ventilation of engine compartment
 Exchanger for hot water (Owner's version, optional engine)
 Maximum engine power 30hp
 Illumination of engine compartment
 Water intake under engine with quarter-turn cock

Remote controls in cockpit
 Dashboard in cockpit with fuel gauge
 Dash features plexiglass cover

Also supplied

Maintenance manual
 Hot water pipe system is installed as standard (Owner's version)

Rigging

Anodised aluminium main mast and boom
 Double level of spreaders
 Backstay turnbuckle
 Spinnaker pole track
 Reefing winch on mast
 Clew outhaul led back to cockpit
 1 jib and mainsail halyard led back to cockpit
 Reef-band
 1 boom topping lift
 Deck floodlight
 Steaming light - Masthead light - Navigation lights on pulpit

Boom downhaul led back to cockpit
 Genoa sheets
 Mainsheet
 3 winch handles

Shroud rigging :
 1 forestry with adjuster battens
 1 inner forestry with stainless steel turnbuckle
 2 aft lower shrouds with stainless steel turnbuckles
 4 upper shrouds with stainless steel turnbuckles
 Shroud and upper shroud turnbuckles affixed to stainless steel chumplates
 Stainless steel chumplates are anchored through reinforcements onto the deck and the hull

Sails supplied

1 mainsail
 1 genoa
 1 storm jib
 Bags

Optional

Drop keel (refer to price-list)
 Wheel with emergency tiller (refer to price-list)
 2 x 2-speed spinnaker sheet winches
 Spinnaker pole - Spinnaker sheet - Downhaul - Topping lift - Halyard
 Spinnaker pole bell-fitting mounted on track
 Hot water tank 43 L (9.45 imp.galls/11.36 US galls) (Owner's version)

Construction


Yac stiffer, yet stronger, SUN-SHINE's hull is laid up by hand using stratified glass KEVLAR® / PARAWATK SUN-SHINE's interior is teak lined throughout

☉ Trade Mark of the Dupont de Nemours company for its high strength Aramid fibre

Jeannneau recommends



Dealer's stamp




BP 83, 83501 La Herbe Cedex, France - Tel. 5191.06.10 - Telex: Bnpp 711383 F Fax 5167.37.65

R.C. La Roche 546 450 024 B. As models are being continually improved, it is stipulated that this document is not a contractual document and the right to modify specifications of boats without prior notice, and to reserved.

SUN SHINE 38

Designer Tony CASTRO



Specifications

Length over all : 11.65 m (38'2.5")
 Hull length : 11.20 m (36'9")
 Length on waterline L. W.L. : 9.35 m (30'8")
 Max. beam : 3.85 m (12'7.5")
 Max. depth E/K : 1.90 m (6'3")
 Draught L/K : 1.24/2.10 m (4'1"/6'11") (deep/shoal)
 Displacement F/K light : 5400 kgs (11905 lbs approx.)
 Weight F/K ballast : 2280 kgs (5026 lbs approx.)
 Displacement L/K light : 5750 kgs (12677 lbs approx.)
 Weight L/K ballast with drop keel : 2620 kgs (5776 lbs approx.)
 Sleeping accommodation : 6 to 10 people (according to version)
 Homologation : Class 1 - 8/9/10 people
 Tonnage : 12.16 register tons

Sail area

Mainsail : 28 m² (301 sq.ft.)
 Light or medium genoa : 48 m² (517 sq.ft.)
 Intermediatic : 38 m² (409 sq.ft.)
 Jib n° 1 : 28 m² (301 sq.ft.)
 Jib n° 2 : 20 m² (215 sq.ft.)
 Spinnaker : 107 m² (1152 sq.ft.)



SUN SHINE 38

TEAM VERSION

Forward cabin

Double berth
 2.00 m × 1.66 m (6'6.5" × 5'6")
 Mattress with removable fabric covers
 Mattress thickness 10 cms (4")
 Lateral sliding to port and starboard
 (2.00 m × 0.15 m / 6'6.5" × 6")
 Storage lockers, compartmented, beneath berth
 Opening deck hatch
 (0.38 m × 0.50 m / 1'3" × 1'8")
 Night blind
 Double-intensity dome ceiling light
 Thru-deck vent giving continual ventilation

Headlining, light-coloured, colour-fast, rot-proof

Carpeting on sole
 Space-making removable lockhead
 Louvered air vent at foot of door
 Headroom 1.75 m (5'9")

Head/washroom

Laminated teak-lined unit
 Washbasin with shower-head attachment, by foot pump
 Storage space over and under wash-basin unit
 Thru-deck vent giving continual ventilation
 (0.33 m × 0.20 m / 1'1" × 8")
 Double-intensity dome ceiling light
 Manual shower drainage pump, beneath washbasin
 Wooden duckboarding over shower-basin inner liner

Full-length mirror
 12 V power socket
 Marine WC

Sliding separating door with louvered air vent
 Clothes hook, rowel rail, wash-glove hook
 Headroom 1.75 m (5'9")

Gangway

Separating door to forward cabin
 Separating door to head/washroom
 Spacious hanging locker to starboard
 Opening deck port
 (0.33 m × 0.20 m / 1'1" × 8")

Saloon

Body-contoured backrests and seating
 Fabric-covered backrests and seating
 Seating thickness 10 cms (4")
 Settee backrests lift up to form pilot berths
 Storage behind backrests
 Shelving running above backrests along the hull - Bar
 L-seater to port with short arm across forward bulkhead
 Bar built into saloon-hanging locker
 bulkhead
 Opening port
 (0.38 m × 0.50 m / 1'3" × 1'8")
 Night blind

Roof ports with drapes/curtains

Striplight over table
 Grabrail along ceiling above roof ports
 2-leaf table with riddle
 2 fresh-water tanks beneath saloon settees and stowage space
 Teak headlining

Teak surround to roof ports
 Drop keel raising winch beneath central section of table (L/K version)
 Teak floorboarded sole
 Ductbin
 Headroom 1.83 m-1.75 m (6' × 5'9")

Electrics panel

Illuminated visualisation of the different electrics on the boat
 11 thermostatic circuit-breakers
 Load tester for the two batteries
 3 battery cut-offs at the foot (to port) of the companionway
 8 switches covering each electrical function
 2 batteries with an electronic load dispatcher

Galley

Functional L-shaped arrangement of units
 Double-sink (stainless steel)
 0.24 m × 0.34 m (9.5" × 11.5")
 Fresh water by pressure pump
 Sea water, by foot pump, separate system
 3 drawers under starboard sink under roof screen
 Storage lockers beneath sink unit (port) with waste-bin, shelving, coaks
 Compartment ice-box with inner basket
 60 mm thick injected polyurethane foam insulation
 2-burner cooker with oven (incorporating safety device), gimballled, with lock

Navigation station

Chart table 1.06 m × 0.68 m (3'6" × 2'3")
 Chart reading light
 Dome ceiling light
 Large panel to house navigational equipment
 Cubby-holes
 Library shelving
 Locker beneath seat
 Bilge pump in locker under table also acts as oilskins locker
 Stainless steel fuel tank beneath table with shut-off cock
 Navigator seat is shaped and teak banded
 Grabrail

Navigation station

Charcoal on ceiling above roof ports
 2-leaf table with riddle
 2 fresh-water tanks beneath saloon settees and stowage space
 Teak headlining
 Teak surround to roof ports
 Drop keel raising winch beneath central section of table (L/K version)
 Teak floorboarded sole
 Ductbin
 Headroom 1.83 m-1.75 m (6' × 5'9")

Spinnaker fittings (optional)

Halvards with stainless steel swift snap shackle and swivel
 Sheers with stainless steel swift snap shackle and swivel
 Downhaul with stainless steel swift snap shackle and swivel
 Topping lift with stainless steel swift snap shackle and swivel
 Anodised aluminium spinnaker pole
 2 × 2-speed spinnaker sheet winches
 Spinnaker sheet return block

Cockpit locker starboard

Compartmented locker comprising
 Storage for gas bottle with vent
 Cubby-hole
 Section for hot water tank (owner's version)

Cockpit locker port aft quarter

Spacious locker for common sailing items
 Storage space for companionway hatch (owner's version)

Liferaft locker beneath helmaman's seat

Teak banded cockpit

Cubby-holes for which handles built into the cockpit seat backrests
 Every locker is lockable

Headroom

Team version
 Forward cabin 1.75 m (5'9")
 Washroom/head 1.75 m (5'9")
 Gangway 1.75 m (5'9")
 Saloon 1.83 m / 1.75 m (6' / 5'9")
 Companionway 1.86 m (6'1")
 Galley and 1.80 m (5'11")
 Navigation station 1.80 m (5'11")
 Aft cabins 1.80 m (5'11")

Owner's version

Forward cabin 1.75 m (5'9")
 Forward cabin 1.83 m / 1.75 m (6' / 5'9")
 Saloon 1.80 m (5'11")
 Galley 1.86 m (6'1")
 Companionway 1.80 m (5'11")
 Washroom/head 1.80 m (5'11")
 Aft cabin 1.80 m (5'11")

Capacities


Team version
 Non-rigid water tanks 2 × 100 L (2 × 22 imp.galls / 2 × 26.42 US galls)
 Diesel 85 L (18.69 imp.galls / 22.45 US galls)
 Inboard battery 70 A/H
 Engine battery 70 A/H
 Loc-box 100 L (3.5 cu.ft.)
 Alternator power 55 A/H
 3 GM Yanmar

Owner's version

Stainless steel water tank 2 × 100 L (2 × 22 imp.galls / 2 × 26.42 US galls)
 Diesel 85 L (18.69 imp.galls / 22.45 US galls)
 Inboard battery 70 A/H
 Engine battery 70 A/H
 Loc-box 100 L (3.5 cu.ft.)
 Alternator power 55 A/H
 Hot water tank 43 L (9.45 imp.galls / 11.36 US galls)
 3 GM Yanmar

SUN SHINE 38

DECK LAYOUT - TEAM AND OWNERS



- 1 Sternhead fitting with bow-roller, chain stop, forestay tang and tack champlet
- 2 Forward pulpit with bow lights
- 3 Forward mooring cleat
- 4 Forward cabin opening deck hatch
- 5 5 through ventilators
- 6 Opening deck hatches
- 7 Mast step
- 8 Saloon opening portlight
- 9 Grab-rail
- 10 3 cam-blockers for boom downhaul, jib and main halwards
- 11 2-speed winch with cleat
- 12 Main traveller
- 13 Location of steering wheel * with column-mounted compass
- 14 Aft mooring cleat
- 15 Chain locker with padlockable cover
- 16 Stanchion bases
- 17 Champlet
- 18 Foot blocks
- 19 Grab-rail
- 20 Sliding companionway hatch
- 21 Genoa sheet track
- 22 2-speed genoa sheet winch
- 23 Sail locker
- 24 Aft pulpit
- 25 Fairlead
- 26 Track-started transom extension with step, shower facility
- 27 Bathing ladder

Companionway

Companionway hatch in two parts
Sliding deck hatch made of Alinglas
Rubber sealing strip
4 companionway steps with non-slip pads and footholds
2 grabrails down companionway steps
Storage for small equipment at the height of the first step
Engine extinguisher, this storage space
3 fast steps angled allowing access to engine compartment
Battery cut-offs at the foot of the companionway steps (portside)

Black plug removable in case of fire (extinguisher nozzle entry)
Headroom 1,80 m (6'1")

Aft quarter cabins (port and starboard)


Double berth (port)
1,95 m x 1,50 m (6'5" x 4'11")
Double berth (starboard)
1,95 m x 1,55 m (6'5" x 5'1")
Mattresses with removable fabric covers
Mattress thickness 10 cms (4")
Storage lockers, compartmented, beneath berths
Double intensity dome ceiling light
Hanging locker
Lateral shelving along bed (aft-side)
1,20 m x 0,25 m (3'11" x 10")

Roof port with drape/curtain
Opening deck port to cockpit
0,10 m x 0,32 m (4" x 1',5")
Louvered air vent at foot of door
Headlining, light coloured, colour-fast, ropeport
Carpeting on sole
Continual ventilation by vent to outside (starboard)
Access to stuffing-box beneath aft berth
Headroom 1,80 m (5'11")

- 1 Sail-storage lockers
- 2 Sail-storage lockers
- 3 Aft cabin storage shelves
- 4 Aft cabin berth
- 5 Aft cabin berth

- 6 Hanging locker
- 7 Galley
- 8 Navigation station
- 9 Upper bunk berths
- 10 Saloon

- 11 Saloon table
- 12 Washroom-head
- 13 Hanging locker
- 14 Forward cabin berth



SUN SHINE 38

OWNER'S VERSION

Forward cabin

Double berth
 1.90 m × 1.68 m (6'3" × 5'6")
 Mattress with removable fabric covers
 Mattress thickness 10 cms (4")
 Removable bedhead forms seat
 Storage at foot of bed
 Lateral shelving to port and starboard
 1.90 m × 0.15 m (6'3" × 6")
 Stowage lockers, compartmented, beneath berth
 Opening deck hatch
 0.38 m × 0.50 m (1'3" × 1'8")
 Night blind
 Dome ceiling light

Drainable spot at bedhead
 Headlining, light-coloured, colour-fast, rotproof
 Locker with shelving and hanging locker
 Washbasin with pressurised hot and cold water tap (Vanity)
 Hot water optional
 Storage space over and under washbasin unit
 Mirror on door of storage over washbasin
 2 thru-deck vents giving continual ventilation
 Louvered air vent at foot of door
 Carpeting on sole
 Headroom 1.75 m (5'9")

Saloon

Body-contoured settee with rounded angles
 Port settee with short arm across saloon-
 forward cabin bulkhead
 Stowage behind backrests
 Sliding running above backrests along the hull
 2 opening deck ports
 0.33 m × 0.20 m (1'1" × 8")
 1 opening port
 0.38 m × 0.50 m (1'3" × 1'8")
 Night blind
 Roof ports with drapes/curtains
 Drape/curtain rods built in under moulding

Grabrails below starboard roof port
 2 dome ceiling lights
 1 built-in strip-light with switch on chart table fiddle
 2 feet table with fiddle
 French-style bread bin under central section of table
 Bar in central section of table
 Handhold separating bulkheads between saloon, galley and navigation station
 2 stainless steel fresh water tanks beneath settee and stowage space
 Hulling of grooved teak

Navigation station

Chart table 0.87 m × 0.73 m (2'10" × 2'5")
 Drivetable chart reading light
 Dome ceiling light
 Large panel to house navigational equipment
 Cabby-hole
 Library shelving
 1 thermosatic circuit-breakers
 Stainless steel diesel tank with shut-off cock
 Bench seat
 Drape/curtain rods built in under moulding
 Roof ports with drapes/curtain
 Drape/curtain rods built in under moulding
 Gradual below port
 Navigator seat in shaped and teak varnished

Panel fixed onto hinged door
 Drivatisation of the different electrics on the boat
 11 thermosatic circuit-breakers
 8 switches covering each electrical function
 Load tester for the two batteries
 3 battery cut-offs beneath has compartmentway step
 Fill check for the two water tanks
 2 batteries with an electronic load dispatcher

Electric panel

Crumbs-tray in sole
 Teak surround to roof ports
 1 built-in strip-light with switch on chart table fiddle
 Headlining of teak and fabric (light coloured, colour-fast, rotproof)
 In ceiling: wires conduit between mast and forward cabin bulkhead concealed behind removable teak panel
 Teak lined mast pillar
 Drop keel raising which beneath central section of table (L/K version)
 Headroom 1.83 m × 1.75 m (6' × 5'9")

Companionway

Sliding deck hatch made of Alurglass
 Rubber sealing strip
 Companionway hatch in two parts with stowage in port locker aft
 4 companionway steps with non-slip pads and footholds
 Access hole for entry to extinguisher nozzle
 2 grabrails down companionway steps
 Child handholds down companionway uprights
 Last two steps removable allowing access to engine compartment
 Battery cut-offs under last step
 Headroom 1.86 m (6'1")

Washroom/Head

Washbasin with shower-head attachment to tap, hot and cold water
 Laminate teak-lined unit with fiddle
 Storage space over washbasin
 Storage space under washbasin with shelving
 Mirror on door of upper storage
 Full-length mirror on bulkhead
 Spacious oilskins locker with drainage
 Duckboard seat folds down onto toilet
 Strip-light over washbasin
 Dome ceiling light
 Roof port with drape/curtain
 Drape/curtain rod built in under moulding
 Opening port onto cockpit with drape/curtain 0.10 m × 0.32 m (4" × 1'5")
 Towel rail
 Hygienic paper holder inside door of oilskins locker
 Clothes hook
 Wash-glove hook
 Shower drainage pump, manual, beneath washbasin
 Wooden duckboarding over shower basin inner liner
 Coats beneath washbasin
 Cigar lighter type 12 V power socket
 Headroom 1.80 m (5'11")

Aft cabin

Double berth
 1.60 m × 1.93 m (5'3" × 6'4")
 Mattress thickness 10 cms (4")
 Compartmented locker beneath berth
 Drivetable reading spotlight at bedhead
 2 dome ceiling lights one of which is over the washbasin unit (vanity)
 Washbasin with pressurised hot and cold water tap
 (hot water optional)
 Storage space over washbasin
 Storage space under washbasin with shelving
 Mirror on door of upper storage
 Hanging locker


Lateral shelving above bed (full-side)
 1.20 m × 0.20 m (3'11" × 8")
 Large panel removed to reveal stowage space over engine
 Roof port with drape/curtain
 Drape/curtain built in under moulding
 2 opening ports onto cockpit with drapes/curtains 0.10 m × 0.32 m (4" × 1'5")
 Louvered air vent at foot of door
 Headlining, light coloured, colour-fast, rotproof
 Access to stuffing-box
 Storage space under washbasin with shelving
 Mirror on door of upper storage
 Headroom 1.80 m (5'11")

Galley

Functional L-shaped arrangement of units
 4 pantry drawers in short arm of galley
 Double-sink (granites steel)
 0.23 m × 0.34 m and 0.30 m × 0.34 m (9" × 1'1.5" and 1' × 1'1.5")
 Pressurised hot and cold water tap
 (Hot water optional)
 Sea water and fresh water by foot pump
 Comfortous storage locker beneath sink unit with waste-bin, shelving, coaks
 Compartmented ice-box with inner basket
 60 cm thickness of injected polyurethane foam insulation

2 burner cooker with oven (incorporating safety device), gimballled, with lock
 Wooden protective grabrail along front of cooker
 Fold-down board to cover hob
 12 V power socket (cigar lighter-type)
 Fiddle around galley work surfaces
 Cookery and storage lockers above cookers and ice-box
 Cookery: 18 plates, 8 dishes, 8 goblets, 8 bowls
 Cutlery: 8 knives, 8 forks, 8 teaspoons, 8 dessert spoons, Cutlery tray

Dome ceiling light
 Roof port with drape/curtain
 Drape/curtain rod built in under moulding
 Teak floorboarded sole
 Headroom 1.80 m (5'11")



- 1 Sail-storage locker
- 2 Aft cabin storage shelves
- 3 Aft cabin berth
- 4 Aft cabin washbasin and hanging locker
- 5 Washroom-head
- 6 Galley
- 7 Navigation station
- 8 Storage shelves
- 9 Saloon
- 10 Saloon table
- 11 Forward cabin washbasin and hanging locker
- 12 Forward cabin storage shelves
- 13 Forward cabin berth